



**TECHNICAL PRODUCT SPECIFICATIONS
RIGID COMPOSITE VINYL PLANK
STYLE**

SPECIFICATIONS:

STYLE NAME	STYLE
LOCKING SYSTEM	DREAMCLICK
FINISH	EIR
BEVEL	4 SIDED MICRO BEVEL
NOMINAL WEAR LAYER THICKNESS	22 MIL (0.55MM)
NOMINAL PRODUCT THICKNESS	5.0 MM (0.2 in)
NOMINAL PLANK SIZE	8.03" W X 52.20" L X 0.20" H
UNIQUE PLANKS PER SKU	8
PIECES PER CARTON	8
SQUARE FEET PER CARTON	23.29 SQ. FT.
APPROX. WEIGHT PER CARTON	34.02 LBS
CARTON SIZE	8.82" W X 53.39" L X 1.61" H
CARTONS PER PALLET	56
SQUARE FEET PER PALLET	1,304.24 SQ. FT.
APPROX. WEIGHT PER PALLET	1,905 LBS.
PALLETS PER 40 FT. CONTAINER	22
SQUARE FEET PER 40 FT. CONTAINER	28,693.28 SQ. FT
APPROX. WEIGHT PER 40 FT. CONTAINER	41,913 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

PERFORMANCE:

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 0.4 K.V. OR LOWER
ORTHO PHTHALATE FREE	ASTM C1028 SCOF - DRY 0.77
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES ≤ 1200 LBS.
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F2753 ROLLING LOADS - PASSES
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 48,600 CYCLES
ASTM E90 - STC RATING 53	ASTM E492 - IIC RATING 47

INSTALLATION:

END USE	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED	UNDERLAYMENT NO MORE THAN 1.5 MM THICKNESS

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR AND MANUFACTURING DEFECT WARRANTY
-------------------------------------------------------------------------------------------	-------------------------------------------------------------------------

DESIGN	MATERIAL NUMBER	EAN/UPC
Elegant Medium Grey	60001564	5414404227881
Elegant Light Greige	60001561	5414404227850
Elegant Natural	60001562	5414404227867
Elegant Natural Brown	60001563	5414404227874
Elegant Dark Grey	60001565	5414404227898
Elegant Light Grey	60001560	5414404227843
Cracked Natural Brown	60001567	5414404227911
Cracked Dark Brown	60001367	5414404222480
Cracked Greige	60001566	5414404227904
Cracked Ash Grey	60001568	5414404227928
Rustic Dark	60001573	5414404227973
Vivid Natural	60001570	5414404227942

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil.
Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.
For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop.