



**TECHNICAL PRODUCT SPECIFICATIONS
COMMERCIAL VINYL SHEET
XTREME**

SPECIFICATIONS:

STYLE NAME	XTREME
FINISH	PU LACQUER
PATTERN REPEAT	REFER TO DESIGN CHART BELOW
NOMINAL WEAR LAYER THICKNESS	28 MILS (0.7 MM)
NOMINAL PRODUCT THICKNESS	80 GAUGE (2 MM)
BACKING TYPE	SOLID BAC
AVAILABLE WIDTH	13'2"
STANDARD ROLL LENGTH (TOLERANCES APPLY)	72 FT.
WEIGHT PER SQUARE YARD	5.09 LBS/SQ. YD.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

PERFORMANCE:

ASTM F1303 TYPE 1 GRADE 1 CLASS C	AATCC 134 (STEP) ELECTROSTATIC 0.2 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM D2047 SCOF - DRY 0.97 WET 0.93
CPSC-CH-C1001-09.3 PHTHALATES - MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F963 HEAVY METAL CONTENT ANALYSIS - PASSES	ASTM D4060 ABRASION RESISTANCE - 28,000 CYCLES
WATER PENETRATION IMPACT - 10,000 CYCLES - PASSES	CAL 1350 EMISSIONS TEST - PASSES
ASTM F2753 ROLLING LOAD - 500 CYCLES - PASS	ISO 4918 CASTOR CHAIR TEST 50,000 CYCLES - PASS
STATIC DECAY TEST 4046 FED STD 101B NFPA 99 0.12 SECONDS	WHEEL CHAIR RESISTANCE - INITIATE 0.5 LBS MAINTAIN 0.1 LBS

INSTALLATION:

END USE	COMMERCIAL
INSTALLATION METHOD	DIRECT GLUE DOWN (CAN BE WELDED)
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED:	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER, COLD WELD, OR HOT WELD.

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	15 YEAR LIMITED COMMERCIAL WEAR, MANUFACTURING DEFECT WARRANTY
---	--

DESIGN	NUMBER	PATTERN REPEAT
GOLDEN OAK 690L	50039881	39.37" W x 39.37" L
HAVANNA OAK 662M	50039879	39.37" W x 59.10"L
MAPLE PLANK 600S	50039875	39.37" W x 39.37"L
MIRA 707M	50039905	ALL OVER
MIRA 690D	50039908	ALL OVER
MIRA 970M	50039909	ALL OVER
MIRA 160L	50039911	ALL OVER
MIRA 116L	50039912	ALL OVER
MIRA 190L	50039913	ALL OVER
NATURAL BEECH 662L	50039876	39.37" W x 39.37" L
NATURAL OAK 369M	50039882	39.37" W x 39.37"L
PURE OAK 904M	50039891	39.37" W x 39.37"L

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.

For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop

877.362.5562

One Beauflor Way
White, GA 30184
United States