



Beaulieu  
International  
Group

Needle Felt

ISO 9001: 2015 CERTIFIED  
ISO 14001: 2015 CERTIFIED

# COLLECTION AUCKLAND RAIL



Pile content	Polmaterial	Composition des fibres	-	<b>100% PP</b>
Surface aspect	Oberflächenstruktur	Aspect du surface	-	<b>Rib</b>
Backing	Rücken	Dossier	ISO 2424	<b>Resine</b>
Pile weight	Polgewicht	Poids des fibres	ISO 8543	<b>1040 gr/m<sup>2</sup></b>
Total weight	Gesamtgewicht	Poids total	ISO 8543	<b>1240 gr/m<sup>2</sup></b>
Pile height	Polhöhe	Hauteur du velours	ISO 1765	<b>4 mm</b>
Total height	Gesamthöhe	Hauteur totale	ISO 1765	<b>9 mm</b>
Roll length	Länge	Longueur	-	<b>30 m</b>
UV stability	UV-Stabilität	Stabilité UV	-	<b>5000 hours</b>
Impact noise reduction	Trittschallminderung	Réduction du bruit d'impact	EN-ISO 140-8	<b>24 dB</b>

## CONTACT

Sales.BFSEurope@bintg.com  
www.beaulieu-needlefelt.com

We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions.  
© Beaulieu International Group

# AUCKLAND RAIL



2035  
Antracite  
2 m



2055  
Black  
2 m



5025  
Lagoon  
2 m



7024  
Brown  
2 m