



**TECHNICAL PRODUCT SPECIFICATIONS
COMMERCIAL VINYL SHEET
BLACKTEX**

SPECIFICATIONS:

STYLE NAME:	BLACKTEX
PATTERN REPEAT	REFER TO DESIGN CHART BELOW
NOMINAL WEAR LAYER THICKNESS	16 MILS
NOMINAL PRODUCT THICKNESS	110 GAUGE
BACKING TYPE	TEX BAC
AVAILABLE WIDTH	13'2"
STANDARD ROLL LENGTH (TOLERANCES APPLY)	99 FT.
WEIGHT PER SQUARE YARD	3.62 LBS/SQ. YD.
COUNTRY OF ORIGIN	MANUFACTURED IN USA

PERFORMANCE:

ASTM F1303 TYPE 1 GRADE 2 CLASS A	AATCC 134 (STEP) ELECTROSTATIC 0.1 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM C1028 SCOF - DRY 0.75
CPSC-CH-C1001-09.3 PHTHALATES - MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F963 HEAVY METAL CONTENT ANALYSIS - PASSES	ASTM D4060 ABRASION RESISTANCE - 65,000 CYCLES
WATER PENETRATION IMPACT - 10,000 CYCLES - PASSES	ASTM E492 IIC 56 ASTM E2179 DELTA 19 ASTM E413 STC52

INSTALLATION:

END USE:	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD:	DIRECT GLUE DOWN , FLOAT UNDER 500 SQ. YDS.
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED:	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER, OR TYPE T COLD WELD

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF, RIP/TEAR/GOUGE WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR, MANUFACTURING DEFECT WARRANTY
---	--

DESIGN	NUMBER	PATTERN REPEAT	DESIGN	NUMBER	PATTERN REPEAT
AVALON 637D	50035857	39.37" W x 39.37"L	IDAHO 617M	50035865	39.37" W x 39.37"L
AVALON 170L	50035858	39.37" W x 39.37" L	IDAHO 960M	50035864	39.37" W x 39.37"L
AVALON 679M	50035859	39.37" W x 39.37"L	LIME OAK 616D	50035867	39.37" W x 59.10"L
DRIFTWOOD 179L	50035875	39.37" W x 59.10"L	LIME OAK 691D	50035868	39.37" W x 59.10"L
GALENA 910L	50035861	39.37" W x 39.37"L	LIME OAK 917M	50035866	39.37" W x 59.10"L
GALENA 941D	50035862	39.37" W x 39.37"L	LIME OAK 970E	50035876	39.37" W x 59.10"L
GALENA 947M	50035863	39.37" W x 39.37"L	SCRUB HICKORY 639D	50035874	39.37" W x 59.10"L
GALENA 961D	50035860	39.37" W x 39.37" L	SCRUB HICKORY 976M	50035873	39.37" W x 59.10"L
HAVANNA OAK 162M	50035869	39.37" W x 59.10"L	TEXAS OAK 646D	50035872	39.37" W x 59.10"L
HAVANNA OAK 916M	50035870	39.37" W x 59.10"L	TEXAS OAK 967M	50035871	39.37" W x 59.10"L

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.

For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop