



TECHNICAL PRODUCT SPECIFICATIONS
CUSHION VINYL SHEET
OMEGA+

SPECIFICATIONS:

STYLE NAME	OMEGA+
FINISH	NATURQUEST- ENHANCED EMBOSS TECHNOLOGY/ PU LACQUER
PATTERN REPEAT	REFER TO DESIGN CHART BELOW
NOMINAL WEAR LAYER THICKNESS	10 MILS (0.25 MM)
NOMINAL PRODUCT THICKNESS	140 GAUGE (3.55 MM)
BACKING TYPE	POWERBAC
AVAILABLE WIDTH	12'
STANDARD ROLL LENGTH (TOLERANCES APPLY)	92 FT.
WEIGHT PER SQUARE YARD	3.539 LBS/SQ. YD.
COUNTRY OF ORIGIN	MANUFACTURED IN USA OF GLOBAL COMPONENTS

PERFORMANCE:

ASTM F1303 TYPE 1 GRADE 3 CLASS C	AATCC 134 (STEP) ELECTROSTATIC 0.8 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM C1028 SCOF – DRY .75 WET .68
CPSC-CH-C1001-09.3 PHTHALATES – MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX – CLASS 1	ASTM F137 FLEXIBILITY – PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY – UNDER 450	ASTM F925 CHEMICAL RESISTANCE – PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E – PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F963 HEAVY METAL CONTENT ANALYSIS - PASSES	ASTM D4060 ABRASION RESISTANCE – 24,000 CYCLES
WATER PENETRATION IMPACT – 10,000 CYCLES - PASSES	100% RECLAIMABLE

INSTALLATION:

END USE	RESIDENTIAL
INSTALLATION METHOD	DIRECT GLUE DOWN/LOOSE LAY UP TO 25 SQ YD/225 SQ FT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO HS RESILIENT SPRAY, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER, BEAUFLO CV SEAM SEALER.

WARRANTIES:

25 YEAR LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY
--

ODYSSEY OAK COFFEE	50047117	39.37" x 59.10"	COSMOS STONE	50047124	39.37" x 39.37"
ODYSSEY OAK OAT	50046720	39.37" x 59.10"	COSMOS LATTE	50046714	39.37" x 39.37"
MOONWOOD BURLAP	50047136	39.37" x 59.07"	COSMOS SMOKE	50047125	39.37" x 39.37"
MOONWOOD CLOUD	50047137	39.37" x 59.07"	STARDUST GINGER	50046723	39.37" x 39.37"
PANDORA BONE	50046721	78.28" x 59.10"	STARDUST SILVER	50047132	39.37" x 39.37"
PANDORA MINK	50046722	78.28" x 59.10"	STARDUST CHARCOAL	50047130	39.37" x 39.37"
STELLAR OAK PEANUT	50047120	78.28" x 59.10"	ASTRID SAND	50047133	78.28" x 59.10"
STELLAR OAK FOG	50047121	78.28" x 59.10"	ASTRID OYSTER	50046719	78.28" x 59.10"
STELLAR OAK CREAM	50047122	78.28" x 59.10"	EARTHBOUND FOSSIL	50047138	39.37" x 39.37"
ECLIPSE PEARL	50046717	39.37" x 39.37"	VEGA OAK PECAN	50046716	39.37" x 59.10"
ECLIPSE AMBER	50046718	39.37" x 39.37"	NEBULA ASH	50046715	39.37" x 39.37"

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.
For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop.