ULTRAGRIP
THE ULTIMATE IN LUXURY VINYL FLOORING
New Collections **2021**
Ultra Hygienic | **Ultra** Slip Resistant | **Ultra** Durable | **Ultra** Water Resistant

ULTRAGRIP

THE ULTIMATE IN LUXURY VINYL FLOORING

Entice

10 YEAR RESIDENTIAL WARRANTY

Page 4 - 15

Empress

15 YEAR RESIDENTIAL WARRANTY | 5 YEAR COMMERCIAL WARRANTY

Page 16 - 27

Eminence

15 YEAR RESIDENTIAL WARRANTY | 5 YEAR COMMERCIAL WARRANTY

Page 28 - 37

Create an impact

When you enter a room, one of the first things you see is the floor covering. It is a fundamental part of the decor, which makes a statement about who you are, so it has to reflect your personality. This is something the designers at Beauflor understand thoroughly. That's why they have spent a lot of time incorporating the latest trends in interior design into the new Ultragrip collections.

Minimalism is out and Victoriana is back. The new Entice and Empress collections both feature several designs inspired by traditional Victorian tiled floors, brought to life by stunning High Definition printing and incredible 3D effects. As well as providing the opportunity to introduce a more vibrant colour palette, the geometric shapes and intricate patterns provide endless design opportunities. Follow the rules to create the classic look or let your imagination run wild and create a unique feature floor for your kitchen or bathroom!

The Empress collection adds a new dimension to luxury vinyl flooring, where exquisite marble and clean cut concrete designs sit alongside distinguished Victorian tile motifs.

Eminence is Beauflor's elegant wood collection, where you will find a wide range of timber effects in different colour ways. Extra-large patterns are in vogue at the moment, so you will find several long plank sizes in this new collection to give your living space a more authentic and luxurious look. Authentically reproduced, using the latest digital printing techniques, they are almost indistinguishable from the real thing.

See the impact for yourself

Ultra Hygienic | **Ultra** Slip Resistant | **Ultra** Durable | **Ultra** Water Resistant

Designed for contemporary interiors, Ultragrip is not just striking to look at, it is practical and versatile too. Ultra Water Resistant, Ultra Slip Resistant, Ultra Durable and Ultra Hygienic - it is ideal for trendsetting home interiors such as bathrooms, kitchens and open plan spaces as well as for retail and hospitality.

All collections have a strong textile backing, which absorbs sound and is warm to walk on, which improves the way you enjoy the space. It also smooths out any irregularities in the sub-floor, which means that often no preparatory work is needed and it can be loose-laid, without glue - saving you time and money!

Ultragrip is highly scuff, scratch and stain resistant, perfect for high traffic areas like walkways and corridors. The hygienic PU lacquer is anti-allergenic, ideal for pet owners. It is also slip resistant and therefore perfect for families with small children or for older people who are nervous on wet surfaces.

Great to look at, easy to install and easy to maintain, Ultragrip floor coverings are environmentally friendly and guaranteed for up to 15 years - why look any further!

TEX BAC TEXTILE BACKING

SLIP RESISTANCE R10 CLASSIFICATION

Ortho-phthalates free

View our Installation & Maintenance Guidelines

www.ultragripbybeauflor.co.uk

ALMERI 001L

Tile Size: 25 x 25 cm

Entice

NICE 077M

Tile Size: 16,5 x 16,5 cm

PIANO 370M

Tile Size: 25 x 25 cm

MARSEILLE 730M

Allover Design

NÎMES 770M

Tile Size: 14 x 14 cm

NÎMES 440M

Tile Size: 14 x 14 cm

WELLS 472M

Tile Size: 20 x 20 cm



DOWNTOWN 228M

Tile Size: 16,5 x 16,5 cm

BIJOUX 900D

Tile Size: 20 x 20 cm

Entice

Product overview

WELLS 472M

Tile size: 20 x 20 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

MARSEILLE 740M

Pattern: Allover
Repeat: 200 x 100 cm
2 - 3 - 4 m

NÎMES 440M

Tile size: 14 x 14 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

NÎMES 770M

Tile size: 14 x 14 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

BIJOUX 070L

Tile size: 20 x 20 cm
Repeat: 100 x 100 cm
2 - 3 - 4 m

DOWNTOWN 228M

Tile size: 16,5 x 16,5 cm
Repeat: 100 x 100 cm
2 - 3 - 4 m

MARSEILLE 730M

Pattern: Allover
Repeat: 200 x 100 cm
2 - 3 - 4 m

ANNECY 072M

Tile size: 17,5 x 17,5 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

ANNECY 909M

Tile size: 17,5 x 17,5 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

NICE 040M

Tile size: 16,5 x 16,5 cm
Repeat: 100 x 100 cm
2 - 3 - 4 m



ALMERI 001L

Tile size: 25 x 25 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

PIANO 370M

Tile size: 25 x 25 cm
Repeat: 100 x 100 cm
2 - 3 - 4 m

NICE 077M

Tile size: 16,5 x 16,5 cm
Repeat: 100 x 100 cm
2 - 3 - 4 m



BIJOUX 900D

Tile size: 20 x 20 cm
Repeat: 100 x 100 cm
2 - 3 - 4 m

Features

Thickness: 2,50 mm | **Wear Layer: 0,25 mm**

ANNECY 072M

Tile Size: 17,5 x 17,5 cm

SNOWSHILL 370M

Tile Size: 20 x 20 cm

SWANSEA 079M

Tile Size: 16,5 x 16,5 cm

ANNECY 170M

Tile Size: 17,5 x 17,5 cm

HAMILTON 127M

Tile Size: 25 x 25 cm

ZURICH 996D

Tile Size: 33 x 33 cm

NOTTINGHAM 971M

Allover Design

Empress

WOLVERHAMPTON 196M

Tile Size: 28,5 x 50 cm

ELBURG 099M

Allover Design

Empress

PRESTON 996D

Tile Size: 25 x 50 cm

Empress

Product overview

SWANSEA 079M

Tile size: 16,5 x 16,5 cm
Repeat: 200 x 200 cm
2 - 3 - 4 m

SNOWSHILL 370M

Tile size: 20 x 20 cm
Repeat: 200 x 200 cm
2 - 3 - 4 m

ANNECY 170M

Tile size: 17,5 x 17,5 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

HAMILTON 127M

Tile size: 25 x 25 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

ZURICH 996D

Tile size: 33 x 33 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

ZURICH 999D

Tile size: 33 x 33 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

NOTTINGHAM 119M

Pattern: Allover
Repeat: 100 x 100 cm
2 - 3 - 4 m

NOTTINGHAM 971M

Pattern: Allover
Repeat: 100 x 100 cm
2 - 3 - 4 m

PRESTON 996D

Tile size: 25 x 50 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

ELBURG 099M

Pattern: Allover
Repeat: 200 x 100 cm
2 - 3 - 4 m

WOLVERHAMPTON 196M

Tile size: 28,5 x 50 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

CLARKSON 169M

Pattern: Allover
Repeat: 200 x 200 cm
2 - 3 - 4 m

WOLVERHAMPTON 639M

Tile size: 28,5 x 50 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

CLARKSON 327M

Pattern: Allover
Repeat: 200 x 200 cm
2 - 3 - 4 m

Features

Thickness: 2,80 mm | **Wear Layer: 0,40 mm**

BLACK TEX BAC · DIN 51130 R10 CLASSIFICATION · PENDULUM TEST >45 · PU LAQUER · SLIP RESISTANT · NATURAL LOOK · 15 YEARS WARRANTY RESIDENTIAL · 5 YEARS WARRANTY COMMERCIAL · UNDERFLOOR HEATING

Ortho-phthalates free



CLARKSON 327M
Allover Design

CROUCH OAK 614M

Plank Size: 20 x 150 cm

LAUREL OAK 116L

Plank Size: 10 x 47 cm

XXL PLANK SIZE

MAJOR OAK 381M

Plank Size: 20 x 200 cm

OAKLAND 166M

Plank Size: 16,6 x 120 cm

OAKLAND 696D

Plank Size: 16,6 x 120 cm

PACIFIC OAK 268M

Plank Size: Diff. Widths x 200 cm

XXL PLANK SIZE

XXL PLANK SIZE

PACIFIC OAK 697D

Plank Size: Diff. Widths x 200 cm

Eminence

Product overview

LAUREL OAK 669D

Plank size: 10 x 47 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

LAUREL OAK 116L

Plank size: 10 x 47 cm
Repeat: 200 x 100 cm
2 - 3 - 4 m

OAKLAND 166M

Plank size: 16,6 x 120 cm
Repeat: 100 x 120 cm
2 - 3 - 4 m

OAKLAND 696D

Plank size: 16,6 x 120 cm
Repeat: 100 x 120 cm
2 - 3 - 4 m

OAKLAND 196L

Plank size: 16,6 x 120 cm
Repeat: 100 x 120 cm
2 - 3 - 4 m

CROUCH OAK 170M

Plank size: 20 x 150 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

CROUCH OAK 126M

Plank size: 20 x 150 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

CROUCH OAK 614M

Plank size: 20 x 150 cm
Repeat: 200 x 150 cm
2 - 3 - 4 m

MAJOR OAK 381M

Plank size: 20 x 200 cm
Repeat: 200 x 200 cm
2 - 3 - 4 m

MAJOR OAK 871M

Plank size: 20 x 200 cm
Repeat: 200 x 200 cm
2 - 3 - 4 m

COLUMBIAN OAK 636L

Plank size: 20 x 150 cm
Repeat: 100 x 150 cm
2 - 3 - 4 m

PACIFIC OAK 081M

Plank size: Diff. Widths x 200 cm
Repeat: 200 x 400 cm
2 - 3 - 4 m

PACIFIC OAK 177M

Plank size: Diff. Widths x 200 cm
Repeat: 200 x 400 cm
2 - 3 - 4 m

PACIFIC OAK 268M

Plank size: Diff. Widths x 200 cm
Repeat: 200 x 400 cm
2 - 3 - 4 m

PACIFIC OAK 697D

Plank size: Diff. Widths x 200 cm
Repeat: 200 x 400 cm
2 - 3 - 4 m

Features

Thickness: 2,80 mm | **Wear Layer: 0,40 mm**

BLACK TEX BAC · R10 SLIP RESISTANCE CLASSIFICATION · PENDULUM TEST +45 · PU LAQUER · SLIP RESISTANT · NATURAL LOOK · 15 YEARS WARRANTY · 5 YEARS WARRANTY · FLOOR HEATING

RESIDENTIAL COMMERCIAL

Ortho-phthalates free

COLUMBIAN OAK 636L

Plank Size: 20 x 150 cm

ULTRAGRIP
THE ULTIMATE IN LUXURY VINYL FLOORING

Entice

Technical Specifications

Product Information

Norm	EN ISO 26986			
Intensity of use	ISO 10874 (EN 685)		23 High domestic 31 Moderate commercial	class
Total Thickness	EN ISO 24346 (EN 428)		2,50	mm
Wearlayer	EN ISO 24340 (EN 429)		0,25	mm
Abrasion group	EN 660-2		T	class
Total weight	EN ISO 23997 (EN 430)		1500	g/m²
Standard width	EN ISO 24341 (EN 426)		2 - 3 - 4	m
Standard length	EN ISO 24341 (EN 426)		+/- 25	m

Technical Information

Dimensional stability	EN ISO 23999 (EN 434)		≤ 0,40	%
Curling	EN ISO 23999		≤ 8	mm
Light stability	EN ISO 105 B02		≥ 6/7	degree
Residual indentation	EN ISO 24343-1 (EN 433)		≤ 0,35	mm
Impact sound improvement	EN ISO 717/2		Δ Lw 16	dB
Dynamic coefficient of friction	EN 13893		> 0,6	
Slip resistance (ramp test with oil)	DIN 51130	R10	R10	scale
Reaction to fire Report number ---- VNLF 031380.4	EN 13501-1	Bfl-s1	Bfl-s1	class
Underfloor heating	EN 12667		Suitable	
Thermal resistance	ISO 8302		0,027	m²K/w
Thermal conductivity	EN 12524		0,09	W/m.K
Chemical resistance	ISO 26987 (EN 423)		resistant	
Static Electrical Propensity	EN 1815		< 2kV	On concrete

*Please note that the data given could be imprecise and liable to modifications of a technical nature at any time. The information in these documents is valid from 07/09/2022 and Beaulieu reserves the right to make changes at any moment and without prior notice. Our technology is constantly evolving, so before carrying out any projects we encourage you to contact us to maintain our highest level of standards.

Environment

100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmfull plasticizers

E1 APPROVED LOW EMISSION

E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)

EMISSIONS DANS L'AIR INTÉRIEUR A+ A B C

Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)

100% Ortho-phthalates free
*for all products produced from May 2017 onwards

floor score

BB Ausschuss zur gesundheitlichen Bewertung von Bauprodukten

Slovenian plant Certifié ISO 14001

Slovenian / Belgium plant Certifié ISO 9001

This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment. We are the leaders in terms of the implementation of clean renewable energy sources and we actively work towards the constant improvement of energy saving.

Product Build

1. PU Lacquer
2. Wear layer
3. Design layer
4. Foam layer
5. Impregnation layer
6. Glass fibre interlayer
7. Backing



EN 14041
CE
05
DOP: 450-TC0013-1
B-LG Flooring nv, Nijverheid 442 B - 8710, Wielsbeke, BELGIUM
NB-1534
Resilient floor covering for use within building
Bfl-s1

UK CA

Features

Thickness: 2,50 mm | Wear Layer: 0,25 mm

TEX BAC · SLIP RESISTANCE R10 CLASSIFICATION · PENDULUM TEST +53 · PU LACQUER · SLIP RESISTANT · NATURAL LOOK · 10 YEARS WARRANTY · FLOOR HEATING · Ortho-phthalates free

ULTRAGRIP
THE ULTIMATE IN LUXURY VINYL FLOORING

Empress Eminence

Technical Specifications

Product Information

Norm	EN ISO 26986			
Intensity of use	ISO 10874 (EN 685)		23 Domestic heavy 32 Commercial general 41 Industrial moderate	class
Total Thickness	EN ISO 24346 (EN 428)		2,80	mm
Wearlayer	EN ISO 24340 (EN 429)		0,40	mm
Abrasion group	EN 660-2		T	class
Total weight	EN ISO 23997 (EN 430)		1950	g/m²
Standard width	EN ISO 24341 (EN 426)		2 - 3 - 4	m
Standard length	EN ISO 24341 (EN 426)		+/- 30	m

Technical Information

Dimensional stability	EN ISO 23999 (EN 434)		≤ 0,40	%
Curling	EN ISO 23999		≤ 8	mm
Light stability	EN ISO 105 B02		≥ 6	degree
Residual indentation	EN ISO 24343-1 (EN 433)		≤ 0,20	mm
Impact sound improvement	EN ISO 717/2		Δ Lw 15	dB
Dynamic coefficient of friction	EN 13893		> 0,6	
Slip resistance (ramp test with oil)	DIN 51130	R10	R10	scale
Reaction to fire Report number ---- VNLF 031380.4	EN 13501-1	Bfl-s1	Bfl-s1	class
Underfloor heating	EN 12667		Suitable	
Thermal resistance	ISO 8302		0,018	m²K/w
Thermal conductivity	EN 12524		0,16	W/m.K
Chemical resistance	ISO 26987 (EN 423)		resistant	
Static Electrical Propensity	EN 1815		< 2kV	On concrete

Environment

100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmfull plasticizers

E1 APPROVED LOW EMISSION

E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)

EMISSIONS DANS L'AIR INTÉRIEUR A+ A B C

Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)

100% Ortho-phthalates free
*for all products produced from May 2017 onwards

floor score

BB Ausschuss zur gesundheitlichen Bewertung von Bauprodukten

Slovenian plant Certifié ISO 14001

Slovenian / Belgium plant Certifié ISO 9001

This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment. We are the leaders in terms of the implementation of clean renewable energy sources and we actively work towards the constant improvement of energy saving.

Product Build

1. PU Lacquer
2. Wear layer
3. Design layer
4. Foam layer
5. Impregnation layer
6. Glass fibre interlayer
7. Backing

EN 14041
CE
05
DOP: 450-TC0013-1
B-LG Flooring nv, Nijverheid 442 B - 8710, Wielsbeke, BELGIUM
NB-1534
Resilient floor covering for use within building
Bfl-s1

UK CA

Features

Thickness: 2,80 mm | Wear Layer: 0,40 mm

BLACK TEX BAC · SLIP RESISTANCE R10 CLASSIFICATION · PENDULUM TEST +45 · PU LACQUER · SLIP RESISTANT · NATURAL LOOK · 15 YEARS WARRANTY RESIDENTIAL · 5 YEARS WARRANTY COMMERCIAL · FLOOR HEATING · Ortho-phthalates free

BEAU FLOR®
we decorate your floor

www.ultragripbybeauflor.co.uk

ULTRAGRIP

THE ULTIMATE IN LUXURY VINYL FLOORING

New Collections **2021**

Ultra Hygienic | **Ultra** Slip Resistant | **Ultra** Durable | **Ultra** Water Resistant