



Beaulieu  
International  
Group

Needle Felt

ISO 9001: 2015 CERTIFIED  
ISO 14001: 2015 CERTIFIED

# COLLECTION CHEVY RESINE



Pile content	Polmaterial	Composition des fibres	-	<b>100% PP</b>
Surface aspect	Oberflächenstruktur	Aspect du surface	-	<b>Dilour</b>
Backing	Rücken	Dossier	ISO 2424	<b>Resine</b>
Pile weight	Polgewicht	Poids des fibres	ISO 8543	<b>450 gr/m<sup>2</sup></b>
Total weight	Gesamtgewicht	Poids total	ISO 8543	<b>500 gr/m<sup>2</sup></b>
Pile height	Polhöhe	Hauteur du velours	ISO 1765	<b>3,2 mm</b>
Total height	Gesamthöhe	Hauteur totale	ISO 1765	<b>4 mm</b>
Roll length	Länge	Longueur	-	<b>30 m</b>

## CONTACT

Sales.BFSEurope@bintg.com  
www.beaulieu-needlefelt.com

We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions.  
© Beaulieu International Group

# CHEVY RESINE




1142  
Lightbeige  
4 m



1770  
Burro  
4 m



2216  
Lichtgrijs  
4 m



2236  
Antraciet  
4 m



3353  
Rood  
4 m




3372  
Crushed Berry  
4 m




5507  
Blauw  
4 m



5539  
Blauw  
4 m




5546  
Indi Blue  
4 m



6651  
Groen  
4 m



7729  
Bruin  
4 m



7760  
Chevreuil  
4 m



7764  
Acorn  
4 m