



TECHNICAL PRODUCT SPECIFICATIONS
LUXURY VINYL TILE
PARKWAY PRO CLICK

SPECIFICATIONS:

STYLE NAME	PARKWAY PRO CLICK
LOCKING SYSTEM	VALINGE 2G
FINISH	PU LACQUER
EMBOSSMENT	MEDIUM EMBOSSSED
BEVEL	4 SIDED MICRO BEVEL
BACKING	IXPE PAD (1.0 MM)
NOMINAL WEAR LAYER THICKNESS	12 MILS (0.3 MM)
NOMINAL PRODUCT THICKNESS	3.4 MM + 1.0 MM PAD = 4.4 MM OVERALL THICKNESS
NOMINAL PLANK SIZE	6.95" W X 47.64" L X 0.17" H
PIECES PER CARTON	12
SQUARE FEET PER CARTON	27.60 SQ. FT.
APPROX. WEIGHT PER CARTON	40 LBS.
CARTON SIZE	48.46" X 7.60" X 2.24"
CARTONS PER PALLET	65
SQUARE FEET PER PALLET	1,794 SQ. FT.
APPROX. WEIGHT PER PALLET	2,650 LBS.
PALLETS PER 40 FT. CONTAINER	15
SQUARE FEET PER 40 FT. CONTAINER	26,910 SQ. FT.
APPROX. WEIGHT PER 40 FT. CONTAINER	39,750 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN VIETNAM

PERFORMANCE:

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 0.8 K.V. OR LOWER
ORTHO PHTHALATE FREE	ASTM C1028 SCOF - DRY 0.63
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES ≤ 1,300 PSI
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 75 MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 17,000 CYCLES

INSTALLATION:

END USE	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR, MANUFACTURING DEFECT WARRANTY
---	--

DESIGN & MATERIAL NUMBER

CLICK COLOR NUMBER

EAN / UPC

DESIGN & MATERIAL NUMBER	CLICK COLOR NUMBER	EAN / UPC
ASH	60001575	190670020993
BARK	60001576	190670021006
BARLEY	60001577	190670021013
CHESTNUT	60001578	190670021020
CINNAMON	60001579	190670021037
GINGER	60001580	190670021044
GUNSTOCK	60001581	190670021051
SAND	60001582	190670021068

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.
For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop.

877.362.5562

One Beauflor Way
White, GA 30184
United States

beauflor.us