# t-profile.
# technical datasheet


BERRY ALLOC

04/2021

## product


**Height adaptable T-profile for BerryAlloc laminate floors, 100% matching the BerryAlloc designs, with exactly the same structure as the floor.**

| | dimensions | weight |
|---|---|---|
| **1 t-profile L1000 mm** | L1000 x W40 x H8 mm | 0,17 kg |
| **1 pack = 1 profile + base + screws&plugs** | L1000 x W50 x H20 mm | 0,32 kg |
| **1 t-profile L2000 mm** | L2000 x W40 x H8 mm | 0,35 kg |
| **1 pack = 1 profile + base + screws&plugs** | L2000 x W50 x H20 mm | 0,65 kg |
| **1 t-profile L2400 mm** | L2400 x W40 x H8 mm | 0,40 kg |
| **1 pack = 1 profile + base + screws&plugs** | L2400 x W50 x H20 mm | 0,75 kg |





Installation: cut the side(s) of the base you do not need, depending on the floor height.


**Total floor + underlay height: 9-10 mm**




**Total floor + underlay height: 11-12mm**




**Total floor + underlay height: 13-15mm**




## product composition

| | |
|---|---|
| **surface** | Direct laminated paper, impregnated with melamine resin. Abrasion class 23/32 AC4. The profiles have exactly the same colour and structure as the laminate floor. |
| **core** | Moisture resistant High Density Fiberboard (HDF). |

## certificates

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+

PEFC Certified
Laminate comes from Sustainably Managed Forests, recycled or controlled sources.
PEFC™
PEFC/07-31-229
www.pefc.org

ÉMISSIONS DANS L'AIR INTÉRIEUR*
A+
A+ A B C
*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

laminate.