Ranger

Gauge	1/5	
Manufacturing	Level loop	
Pile description	PP Tristar	
Primary backing	Woven	
Pile weight	530 gr/m²	
Number of tufts	74.803 /m²	
Secondary backing	Premiumback	
Width	400 cm	500 cm
Total weight	1550 gr/m²	1550 gr/m²
Total height	7 mm	7 mm
Pile In/Out	Out	Out
Roll length	30 m	30 m
DOP	1087#822/RAG/H	
Fire classification	Efl	
Use classification	22	
TOG rating	1	

Available colours	Premiumback I 400/500 cm	116 I 153 I 156 I 157 I 165 I 312 I 333 I 882 I 964 I 994 I 995 I

Colour legend	116	Stone	153	Dark Grey	156	Dolphin
	157	Pebble	165	Graphite	312	Almond
	333	Pecan	882	Ocean	964	Walnut
	994	Beach	995	Coconut		



CE EN 14041 DS EN 1307 A+

These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to modify technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching can not be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.


BIG Floorcoverings nv Rijksweg 442 I 8710 Wielsbeke - Belgium I T +32 (0)56 67 42 11 I F +32 (0)56 67 48 40 I www.ideal-bintg.com

27.09.2018 I ISO N090N02/2/01-01-10


Beaulieu International Group

Ranger






116 - 400/500 cm



153 - 400/500 cm



156 - 400/500 cm



157 - 400/500 cm



165 - 400/500 cm



312 - 400/500 cm



333 - 400/500 cm




882 - 400/500 cm



964 - 400/500 cm



994 - 400/500 cm



995 - 400/500 cm