



TECHNICAL PRODUCT SPECIFICATIONS
LAMINATE PLANK
HYDRANA

SPECIFICATIONS:

STYLE NAME	HYDRANA WATER RESISTANT LAMINATE
ABRASION CLASS	AC5 CLASS 33
LOCKING SYSTEM	VALINGE 5G
FINISH	EIR
BEVEL	4 SIDED PAINTED MICRO BEVEL W/ WATER REPELLANT COATING
NOMINAL PRODUCT THICKNESS	12MM + 2MM PAD = 14MM TOTAL
NOMINAL PLANK SIZE	7.48" W X 50.71"L x .55" H
UNIQUE PLANKS PER SKU	10
PLANKS PER CARTON	5
SQUARE FEET PER CARTON	13.17 SQ. FT.
APPROX. WEIGHT PER CARTON	30.38 LBS.
CARTON SIZE	7.91"W X 51.18" L X 2.60"H
CARTONS PER PALLET	56
SQUARE FEET PER PALLET	737.52 SQ. FT.
APPROX. WEIGHT PER PALLET	1,751.28 LBS.
PALLETS PER 40 FT. CONTAINER	25
SQUARE FEET PER 40 FT. CONTAINER	18,438 SQ. FT.
APPROX. WEIGHT PER 40 FT. CONTAINER	43,782 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

PERFORMANCE:

CARB PHASE II – TSCA Title VI Compliant	ASTM C1028 SCOF – DRY 0.68
ASTM E648 CRITICAL RADIANT FLUX – CLASS 1	NALFA 3.9 CHAIR RESISTANCE – CLASS 4
ASTM E662 SMOKE DENSITY – UNDER 450	NALFA 3.1 STATIC LOAD – CLASS 4
NALFA 3.3 XENON LIGHT RESISTANCE - CLASS 4	NALFA 3.5 LARGE BALL IMPACT RESISTANCE – CLASS 4
NALFA 3.4 CLEANABILITY – STAIN RESISTANCE – CLASS 4	NALFA 3.6 SMALL BALL DART IMPACT – CLASS 4
NALFA 3.7 WEAR RESISTANCE - CLASS 4	AATCC 134 (STEP) ELECTROSTATIC 1.9 K.V.
NALFA 3.10 SURFACE BOND – CLASS 4	NALFA 3.2 THICKNESS SWELL – CLASS 4
NALFA 3.8 DIMENSIONAL TOLERANCE – CLASS 4	NALFA LF-01-2011 CONFORMANCE TESTING – CLASS 4
ASTM E989-06 (IIC) - 58	ASTM E413-16 (STC) - 53

INSTALLATION:

END USE	RESIDENTIAL, COMMERCIAL
INSTALLATION METHOD	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED	6 MM POLYETHYLENE SHEETING

WARRANTIES:

LIMITED LIFETIME RESIDENTIAL WEAR, FADE, STAIN, JOINT & TOPICAL 72 HR MOISTURE WARRANTY	15 YEAR COMMERCIAL WEAR, FADE, STAIN, JOINT & TOPICAL MOISTURE WARRANTY
---	---

DESIGN & MATERIAL NUMBER

PART NUMBER

EAN / UPC NUMBER

CANYON GREY	62001640	5414404225603
CANYON LIGHT GREY	62001642	5414404225610
GYANT DARK BROWN	62001645	5414404225665
GYANT GREY	62001641	5414404225634
GYANT LIGHT GREY	62001639	5414404225627
GYANT LIGHT NATURAL	62001644	5414404225658
GYANT NATURAL	62001643	5414404225641
TEXAS BROWN	62001638	5414404225597

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand. For heavily soiled areas, use a non-abrasive neutral pH cleaner specially formulated for use with laminate and a microfiber mop.

877.362.5562