



TECHNICAL PRODUCT SPECIFICATIONS
LUXURY VINYL TILE
PARKWAY PRO DRY BACK

SPECIFICATIONS:

STYLE NAME	PARKWAY PRO DRY BACK
FINISH	PU LACQUER
EMBOSSMENT	MEDIUM EMBOSSSED
BEVEL	SQUARE EDGES
NOMINAL WEAR LAYER THICKNESS	12 MIL (0.3 MM)
NOMINAL PRODUCT THICKNESS	2.0 MM (0.079")
NOMINAL PLANK SIZE	7.25" W X 48.0" L X 0.080" H
PIECES PER CARTON	15
SQUARE FEET PER CARTON	36.26 SQ. FT.
APPROX. WEIGHT PER CARTON	25.56 LBS.
CARTON SIZE	48.43 " X 7.29 " X 1.22"
CARTONS PER PALLET	72
SQUARE FEET PER PALLET	2,610.72 SQ. FT.
APPROX. WEIGHT PER PALLET	1,890.32 LBS.
PALLETS PER 40 FT. CONTAINER	21
SQUARE FEET PER 40 FT. CONTAINER	54,825.12 SQ. FT.
APPROX. WEIGHT PER 40 FT. CONTAINER	39,696.72 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN VIETNAM

PERFORMANCE:

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 0.4 K.V. OR LOWER
ORTHO PHTHALATE FREE	ASTM C1028 SCOF - DRY 0.63
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES \leq 1300 PSI
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 20,000 CYCLES

INSTALLATION:

END USE	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD	DIRECT GLUE DOWN
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED:	BEAUFLOR 4N1 MULTIPURPOSE ADHESIVE, BEAUFLOR LVT ULTRABOND, BEAUFLOR ISOLATE, BEAUFLOR MOISTURE SEAL 95, BEAUFLOR SUBSTRATE PRIMER

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY 10 YEAR LIGHT COMMERCIAL WEAR, 2 YEAR MANUFACTURING DEFECT

DESIGN & MATERIAL NUMBER	DRY BACK COLOR NUMBER	EAN / UPC
PARKWAY PRO ASH	60001376	190670015951
PARKWAY PRO BARK	60001377	190670015968
PARKWAY PRO BARLEY	60001378	190670015975
PARKWAY PRO CHESTNUT	60001379	190670015982
PARKWAY PRO CINNAMON	60001380	190670015999
PARKWAY PRO GINGER	60001381	190670016002
PARKWAY PRO GUNSTOCK	60001382	190670016019
PARKWAY PRO SAND	60001383	190670016026

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.
For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop