



TECHNICAL PRODUCT SPECIFICATIONS
CUSHION VINYL SHEET
METRO REFRESH

SPECIFICATIONS:

STYLE NAME:	METRO REFRESH
PATTERN REPEAT	REFER TO DESIGN CHART BELOW
NOMINAL WEAR LAYER THICKNESS	10 MILS
NOMINAL PRODUCT THICKNESS	55 GAUGE
BACKING TYPE	POWER BAC
AVAILABLE WIDTH	12'
STANDARD ROLL LENGTH (TOLERANCES APPLY)	131 FT.
WEIGHT PER SQUARE YARD	2.58 LBS/SQ. YD.
COUNTRY OF ORIGIN	MANUFACTURED IN USA

PERFORMANCE:

ASTM F1303 TYPE 1 GRADE 3 CLASS C	AATCC 134 (STEP) ELECTROSTATIC 0.5 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM C1028 SCOF - DRY 0.78
CPSC-CH-C1001-09.3 PHTHALATES - MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F963 HEAVY METAL CONTENT ANALYSIS - PASSES	ASTM D4060 ABRASION RESISTANCE - 18,000 CYCLES
WATER PENETRATION IMPACT - 10,000 CYCLES - PASSE	100% RECLAIMABLE

INSTALLATION:

END USE:	RESIDENTIAL
INSTALLATION METHOD:	DIRECT GLUE DOWN
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED:	BEAUFLOR 4N1 MULTIPURPOSE ADHESIVE, BEAUFLOR HS RESILIENT SPRAY, BEAUFLOR ISOLATE, BEAUFLOR MOISTURE SEAL 95, BEAUFLOR SUBSTRATE PRIMER, BEAUFLOR CV SEAM SEALER.

WARRANTIES:

5 YEAR RESIDENTIAL LIMITED WEAR WARRANTY
--

DESIGN

MATERIAL NUMBER

PATTERN REPEAT

BARNWOOD 164M	50033454	39.37" W x 59.10" L
BARNWOOD 661D	50040728	39.37" W x 59.10" L
HICKORY 119M	50040727	39.37" W x 39.37" L
HICKORY 168M	50033450	39.37" W x 39.37" L
HICKORY 669D	50040705	39.37" W x 39.37" L
HOUSTON 991L	50040707	39.37" W x 39.37" L
HOUSTON 639M	50040732	39.37" W x 39.37" L
HOUSTON 976D	50040733	39.37" W x 39.37" L
NATURAL OAK 664D	50040706	39.37" W x 39.37" L
NATURAL OAK 963M	50040729	39.37" W x 39.37" L
TEXAS OAK 631M	50040730	39.37" W x 59.10" L
TEXAS OAK 996D	50040731	39.37" W x 59.10" L
YELLOW STONE 019S	50033458	39.37" W x 39.37" L
YELLOW STONE 169M	50033459	39.37" W x 39.37" L
YELLOW STONE 619D	50033460	39.37" W x 39.37" L

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.

For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop

877.362.5562

One Beauflor Way
White, GA 30184
United States

beauflor.com