



Rewind® Flat

Latex-free event carpet, 100% recyclable
into a pure high-grade recycle

REWIND®



TECHNICAL DATA	TECHNISCHE DATEN	FICHE TECHNIQUE		
Manufacturing process	Herstellungsart	Méthode de fabrication	DIN 61151	Needle felt
Surface structure	Oberflächenstruktur	Aspect de surface	-	Flat
Pile material	Polmaterial	Composition des fibres	-	100% polypropylene
Pile weight Total weight	Polgewicht Gesamtgewicht	Poids des fibres Poids total	ISO 8453	230 g/m²
Roll length	Rollenlänge	Longueur rouleau	-	50 m
Backing	Rückenbeschichtung	Dossier	ISO 2424	None - latex free
Pile height Total height	Polhöhe Gesamthöhe	Hauteur du velours Hauteur totale	-	2 mm
Permanent anti-static	Permanent antistatisch	Antistatique permanent	ISO 6356	≤ 2kV
Fire Classification	Brennklasse	Comportement au feu	EN 13501-1	Bfl-s1
Prodis GUT Certificate	Prodis GUT Zertifikat	Certificat Prodis GUT	-	943358A6



CONTACT

rewind@bintg.com
www.rewindcarpet.com

A BRAND OF
Beaulieu
International
Group



REWIND® Flat

WITH FILM

WITHOUT FILM

COLOUR NAME		2M	3M	4M	2M	3M	4M
0110*	SNOW WHITE	✓	✓	✓	✓	✓	-
0219*	SAHARA	✓	✓	✓	✓	✓	-
0503*	VIOLET	✓	✓	✓	✓	✓	-
0625*	SPRING GREEN	✓	✓	✓	✓	✓	-
0713*	RED	✓	✓	✓	✓	✓	-
0740*	RUBY RED	✓	✓	✓	✓	✓	-
0809*	SEA BLUE	✓	✓	✓	✓	✓	-
0812*	ROYAL BLUE	✓	✓	✓	✓	✓	-
0840*	AQUA	✓	✓	✓	✓	✓	✓
0851*	PACIFIC BLUE	✓	✓	✓	✓	✓	-
0913	JET BLACK	✓	✓	✓	✓	✓	✓
0923	CHARCOAL	✓	✓	✓	✓	✓	✓
0947	SHADOW GREY	✓	✓	✓	✓	✓	-
0949	FROST GREY	✓	✓	✓	✓	✓	-
0952	SMOKE GREY	✓	✓	✓	✓	✓	✓
0200	BEIGE	✓	-	-	-	-	-
0400*	YELLOW	✓	-	-	-	-	-
0450*	ORANGE	✓	✓	-	-	-	-
0510*	FUCHSIA	✓	-	-	-	-	-
0524*	PLUM	✓	-	-	-	✓	-
0715*	CHILLY RED	✓	-	-	✓	✓	-
0624*	FOREST GREEN	✓	-	-	✓	-	-
0637*	BOTTLE GREEN	✓	-	-	-	-	-
0675*	LIME	✓	-	-	-	-	-
0707*	FIRE RED	✓	-	-	-	-	-
0822*	TURQUOISE	✓	✓	-	✓	✓	-
0842*	MIDNIGHT BLUE	✓	-	-	✓	✓	-
0936	TAUPE	✓	-	-	-	-	-
0939	ASH GREY	✓	-	-	✓	-	-
0960	ELEPHANT GREY	✓	-	-	-	✓	-



Colours may slightly vary from batch to batch. Characteristics in line with EN 1307 standards.
We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions.
© Beaulieu International Group

DNF.RO.MAR.15b/2/15-2-22