



Beaulieu
International
Group

Needle Felt

ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED

COLLECTION CHEVY GEL



Pile content	Polmaterial	Composition des fibres	-	100% PP
Surface aspect	Oberflächenstruktur	Aspect du surface	-	Dilour
Backing	Rücken	Dossier	ISO 2424	Gel
Pile weight	Polgewicht	Poids des fibres	ISO 8543	450 gr/m²
Total weight	Gesamtgewicht	Poids total	ISO 8543	1500 gr/m²
Pile height	Polhöhe	Hauteur du velours	ISO 1765	3,2 mm
Total height	Gesamthöhe	Hauteur totale	ISO 1765	4,5 mm
Roll length	Länge	Longueur	-	30 m

CONTACT

Sales.BFSEurope@bintg.com
www.beaulieu-needlefelt.com

We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions.
© Beaulieu International Group

DNF.RO.MAR.15a/2/15-2-22

CHEVY GEL



1142
Lightbeige
4 m




1770
Burro
4 m



2216
Lichtgrijs
4 m



2236
Antraciet
4 m



3353
Rood
4 m




3372
Crushed Berry
4 m




5507
Blauw
4 m



5539
Blauw
4 m



5546
Indi Blue
4 m



6651
Groen
4 m



7729
Bruin
4 m



7760
Chevreuil
4 m



7764
Acorn
4 m