



**TECHNICAL PRODUCT SPECIFICATIONS**  
**RIGID CORE VINYL PLANK**  
**BOARDWALK COLLECTION**  
**PATH**

**SPECIFICATIONS:**

STYLE NAME	PATH
FINISH	PREMIUM PROTECT STAIN & SCRATCH RESISTANCE
CONSTRUCTION	RIGID CORE WITH ATTACHED IXPE UNDERLAYMENT
LOCKING SYSTEM	VALINGE 5GI
EMBOSSMENT	EIR/MEDIUM EMBOSSSED
BEVEL	PAINTED BEVEL
NOMINAL WEAR LAYER THICKNESS	22 MILS (0.55 MM)
NOMINAL PRODUCT THICKNESS	5.0 MM (4 MM WITH 1 MM IXPE UNDERLAYMENT)
NOMINAL PLANK SIZE	7.01" W X 58.34" L X 0.20" H
PIECES PER CARTON	8
SQUARE FEET PER CARTON	22.88 SQ. FT.
APPROX. WEIGHT PER CARTON	37.83 LBS.
CARTON SIZE	59.5" L X 7.6" W X 1.7" H
CARTONS PER PALLET	70
SQUARE FEET PER PALLET	1,601.60 SQ. FT.
APPROX. WEIGHT PER PALLET	2,698.10 LBS.
PALLETS PER 40 FT. CONTAINER	15
SQUARE FEET PER 40 FT. CONTAINER	24,024 SQ. FT.
APPROX. WEIGHT PER 40 FT. CONTAINER	40,471.50 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN CHINA

**PERFORMANCE:**

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 1.2 K.V. OR LOWER
ORTHO PHTHALATE FREE	ASTM D2047 SCOF - DRY 0.93
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES ≤ 1000 LBS.
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F2199 DIMENSIONAL STABILITY - PASSES
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 40,000 CYCLES

**INSTALLATION:**

END USE	RESIDENTIAL, 3 SEASON ROOM, LIGHT COMMERCIAL
INSTALLATION METHOD	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F

**WARRANTIES:**

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED THREE SEASONS WARP, MANUFACTURING DEFECT WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR, MANUFACTURING DEFECT WARRANTY
-------------------------------------------------------------------------------------------	-------------------------------------------------------------------	----------------------------------------------------------------------

**DESIGN & MATERIAL NUMBER**

**CLICK COLOR NUMBER**

**EAN / UPC**

PATH BREEZE	60001211	190670011823
PATH DEW	60001214	190670011854
PATH MIST	60001213	190670011847
PATH WHISK	60001212	190670011830

**CARE & MAINTENANCE:**

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand. For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop