Perfection

Gauge	3/16
Manufacturing	Cut pile
Pile description	Velluto
Primary backing	Woven
Pile weight	1230 gr/m²
Number of tufts	66.600 /m²
Secondary backing	Premiumback
Width	300/400/500 cm
Total weight	2010 gr/m²
Total height	11,5 mm
Pile In/Out	Out
Roll length	25 m
DOP	1087#220001/PFT/H
Fire classification	Efl
Use classification	22
TOG rating	1,1



Available colours: Premiumback | 300/400/500 cm 109 | 139 | 153 | 155 | 158 | 965 | 966 |

Colour legend

109	Steel	139	Phantom	153	Dark Grey
155	Pigeon	158	Anthracite	965	Beaver
966	Leather				



CE EN 14041 | DS EN 1307 | ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C

These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to modify technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching can not be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

BIG Floorcoverings nv Rijksweg 442 | 8710 Wielsbeke - Belgium | T +32 (0)56 67 42 11 | F +32 (0)56 67 48 40 | www.ideal-bintg.com

28.08.2020 | ISO N090N02/2/01-01-10

Beaulieu International Group

Perfection






109 - 3/4/5 m



139 - 3/4/5 m



153 - 3/4/5 m



155 - 3/4/5 m



158 - 3/4/5 m



965 - 3/4/5 m



966 - 3/4/5 m