



TECHNICAL PRODUCT SPECIFICATIONS  
LAMINATE PLANK  
TRENDLINE PRO

**SPECIFICATIONS:**

STYLE NAME:	TRENDLINE PRO
RECOMMENDED END USE	RESIDENTIAL, COMMERCIAL
WEAR RESISTANCE	AC4   CLASS 32
BEVEL	4 SIDE PAINTED MICRO- BEVEL
NOMINAL PRODUCT THICKNESS	8.0 MM
NOMINAL PLANK SIZE	7.48" W X 50.71" L X 0.31" H
UNIQUE PLANKS PER SKU	10
PLANKS PER CARTON	9
SQUARE FEET PER CARTON	23.707 SQ. FT.
APPROX. WEIGHT PER CARTON	34.61 LBS.
CARTON SIZE	7.91" W X 51.18" L X 2.60" H
CARTONS PER PALLET	56
SQUARE FEET PER PALLET	1,327.59 SQ. FT.
APPROX. WEIGHT PER PALLET	1,988.16 LBS.
PALLETS PER 40 FT. CONTAINER	22
SQUARE FEET PER 40 FT. CONTAINER	29,207.02 SQ. FT.
APPROX. WEIGHT PER 40 FT. CONTAINER	43,739.52 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

**PERFORMANCE:**

CARB PHASE II – TSCA Title VI Compliant	ASTM C1028 SCOF – DRY 0.78
ASTM E648 CRITICAL RADIANT FLUX – CLASS 1	NALFA 3.9 CHAIR RESISTANCE – CLASS 4
ASTM E662 SMOKE DENSITY – UNDER 450	NALFA 3.1 STATIC LOAD – CLASS 4
NALFA 3.3 XENON LIGHT RESISTANCE - CLASS 4	NALFA 3.5 LARGE BALL IMPACT RESISTANCE – CLASS 4
NALFA 3.4 CLEANABILITY – STAIN RESISTANCE – CLASS 4	NALFA 3.6 SMALL BALL DART IMPACT – CLASS 4
NALFA 3.7 WEAR RESISTANCE - CLASS 4	AATCC 134 (STEP) ELECTROSTATIC 1.0 K.V. OR LOWER
NALFA 3.10 SURFACE BOND – CLASS 4	NALFA 3.2 THICKNESS SWELL – CLASS 3
NALFA 3.8 DIMENSIONAL TOLERANCE – CLASS 4	NALFA LF-01-2011 CONFORMANCE TESTING – CLASS 3

**INSTALLATION:**

END USE:	RESIDENTIAL, COMMERCIAL
INSTALLATION METHOD:	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED:	DREAMTEC PROFLOAT UNDERLAYMENT

**WARRANTIES:**

20 YEAR LIMITED RESIDENTIAL WEAR, FADE, STAIN, JOINT & TOPICAL 24 HR MOISTURE WARRANTY	5 YEAR COMMERCIAL WEAR, FADE, STAIN, JOINT & TOPICAL 24 HR MOISTURE WARRANTY
--	--

DESIGN & MATERIAL NUMBER	PART NUMBER	EAN / UPC NUMBER
BAHAMAS OAK	62001637	5414404224620
BRIGHTON OAK	62001634	5414404224590
CAMBRIDGE OAK	62001632	5414404224576
FIJI OAK	62001636	5414404224613
LIVERPOOL OAK	62001633	5414404224583
LONDON OAK	62001635	5414404224606
MAGNOLIA OAK	62001631	5414404224569
VIVALDI OAK	62001630	5414404224552

**CARE & MAINTENANCE:**

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand. For heavily soiled areas, use a non-abrasive neutral pH cleaner specially formulated for use with laminate and a microfiber mop.

Rev. 031221

877.362.5562

One Beauflor Way  
White, GA 30184  
United States

beauflor.us