



Beaulieu
International
Group

Needle Felt

ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED

COLLECTION ULTRACORD



Pile content	Polmaterial	Composition des fibres	-	100% PP
Surface aspect	Oberflächenstruktur	Aspect du surface	-	Rib
Backing	Rücken	Dossier	ISO 2424	Resine
Pile weight	Polgewicht	Poids des fibres	ISO 8543	900 gr/m²
Total weight	Gesamtgewicht	Poids total	ISO 8543	1050 gr/m²
Pile height	Polhöhe	Hauteur du velours	ISO 1765	2 mm
Total height	Gesamthöhe	Hauteur totale	ISO 1765	6 mm
Roll length	Länge	Longueur	-	30 m

CONTACT

Sales.BFSEurope@bintg.com
www.beaulieu-needlefelt.com

We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions.
© Beaulieu International Group

ULTRACORD




1082
Tan
2 m




2063
Dove Grey
2 m




2067
Frost Grey
2 m




2097
Antracite
2 m




3033
Deep Claret
2 m




3053
Cherry
2 m




5026
Blue Bell
2 m




5043
Ocean
2 m



5067
Nautical Blue
2 m



5077
Silver Lake
2 m



6029
Petrol Green
2 m



7755
Safari
2 m