



Product Description

• Dimensions	1285 L x 186 W x 7 TH
• Packaging	Box: 9 boards - 2.15 m ² (14.4 kg) Pallet : 56 boxes - 120.46 m ² (830 kg)
• Density (average)	900 kg/m ³
• Composition	
> Surface layer	Direct Laminated Papers. Paper impregnated with melamine resin
> Substrate	Moisture-resistant High Density Fibreboard, HDF
> Backing	Direct Laminated Paper. Paper impregnated with melamine resin
• Features	Matlook
• Installation	Best Loc: glue-free mechanical locking system produced under license of Välinge Innovation AB, Flooring Industries Ltd and Faus Group Inc
• Installation instruction	see box inlay or www.berryalloc.com

Requirements

- General requirements according to EN13329
- Classification Requirements class 23/32

Characteristics

Method

Result

Abrasion resistance	EN13329	AC4 (IP≥4000)
Impact resistance	EN13329	IC2
Thickness swelling	EN13329	≤ 15%
Resistance to staining	EN438	5 (groups 1+2); 4 (group 3)
Resistance to cigarette burns	EN438	4
Effect of a furniture leg	EN424	No damage (foot type 0)
Effect of a castor chair	EN425	No change in appearance or damage

CE - classification according to EN14041

- Fire resistance C_{fl}-S1
- Formaldehyde E1
- Slipperiness DS

Other technical data

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- CARB: Phase II compliant
- Floor heating: see specific instructions at www.berryalloc.com
- Thermal resistance in combination with underlay Excellence Endurance: 0,09 m² K/W

Warranty and maintenance

- Residential warranty Lifetime
- Commercial warranty 5 years
- Warranty conditions see www.berryalloc.com
- Care and maintenance see www.berryalloc.com

