



Beaulieu
International
Group

Needle Felt

ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED

COLLECTION INDEX RESINE



Pile content	Polmaterial	Composition des fibres	-	100% synthetic
Surface aspect	Oberflächenstruktur	Aspect du surface	-	Rib
Backing	Rücken	Dossier	ISO 2424	Resine
Pile weight	Polgewicht	Poids des fibres	ISO 8543	250 gr/m²
Total weight	Gesamtgewicht	Poids total	ISO 8543	290 gr/m²
Pile height	Polhöhe	Hauteur du velours	ISO 1765	1,5 mm
Total height	Gesamthöhe	Hauteur totale	ISO 1765	3,3 mm
Roll length	Länge	Longueur	-	75 m


CONTACT

Sales.BFSEurope@bintg.com
www.beaulieu-needlefelt.com


We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions.
© Beaulieu International Group

DNF.RO.MAR.15a/2/15-2-22


INDEX RESINE



9260
Beige
2 m - 4 m




9303
Bright Red
2 m - 4 m



9660
Grass
2 m - 4 m



9770
Charcoal
2 m - 4 m



9890
Antraciet
2 m - 4 m




9891
Lever
2 m - 4 m



9892
Lichtgrijs
2 m - 4 m




9895
Lichtblauw
2 m - 4 m




9896
Linde
4 m




9897
Mix Bruin
2 m - 4 m



9899
Groen
2 m - 4 m



9903
Rood
2 m - 4 m



9904
Blauw
2 m - 4 m