



TECHNICAL PRODUCT SPECIFICATIONS
CUSHION VINYL SHEET
GAMMA

SPECIFICATIONS:

STYLE NAME:	GAMMA
PATTERN REPEAT	REFER TO DESIGN CHART BELOW
NOMINAL WEAR LAYER THICKNESS	10 MILS
NOMINAL PRODUCT THICKNESS	110 GAUGE
BACKING TYPE	COMFORT BAC
AVAILABLE WIDTH	13'2"
STANDARD ROLL LENGTH (TOLERANCES APPLY)	98 FT.
WEIGHT PER SQUARE YARD	3.04 LBS/SQ. YD.
COUNTRY OF ORIGIN	MANUFACTURED IN USA OF GLOBAL COMPONENTS

PERFORMANCE:

ASTM F1303 TYPE 1 GRADE 3 CLASS C	AATCC 134 (STEP) ELECTROSTATIC 0.1 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM C1028 SCOF - DRY 0.79
CPSC-CH-C1001-09.3 PHTHALATES - MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F963 HEAVY METAL CONTENT ANALYSIS - PASSES	ASTM D4060 ABRASION RESISTANCE - 18,000 CYCLES
WATER PENETRATION IMPACT - 10,000 CYCLES - PASSES	100% RECLAIMABLE

INSTALLATION:

END USE:	RESIDENTIAL
INSTALLATION METHOD:	DIRECT GLUE DOWN
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED:	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO HS RESILIENT SPRAY, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER, BEAUFLO CV SEAM SEALER.

WARRANTIES:

7 YEAR LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY

DESIGN & MATERIAL NUMBER	13' 2'	PATTERN REPEAT
ELMWOOD 036M	50028720	39.37" W x 39.37" L
ELMWOOD 632D	50028742	39.37" W x 39.37" L
GALENA 639D	50035347	39.37" W x 39.37" L
GALENA 974M	50035346	39.37" W x 39.37" L
HICKORY 679M	50035338	39.37" W x 39.37" L
HICKORY 970M	50035339	39.37" W x 39.37" L
HOUSTON 915L	50035344	39.37" W x 39.37" L
HOUSTON 969M	50035345	39.37" W x 39.37" L
LIME OAK 163M	50035340	39.37" W x 59.10" L
LIME OAK 663M	50028721	39.37" W x 59.10" L
NORDIC WALNUT 634D	50028743	39.37" W x 39.37" L
PARMA 237M	50028724	39.37" W x 39.37" L
TEXAS OAK 312M	50035341	39.37" W x 59.10" L
TEXAS OAK 961D	50035342	39.37" W x 59.10" L
VALLEY OAK 916M	50035343	39.37" W x 59.10" L

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.
For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop