BEAU FLOR®
we decorate your floor

Evasion | TECHNICAL DATA SHEET

PRODUCT INFORMATION

Norm	EN ISO 26986			
Intensity of use	ISO 10874 (EN 685)		23 domestic heavy 31 commercial moderate	class
Total thickness	EN ISO 24346 (EN 428)		2,50	mm
Wear layer	EN ISO 24340 (EN 429)		0,25	mm
Abrasion group	EN 660-2		T	class
Total weight	EN ISO 23997 (EN 430)		1500	g/m²
Standard width	EN ISO 24341 (EN 426)		2 - 3 - 4*	m
Standard length	EN ISO 24341 (EN 426)		+/- 25	m

TECHNICAL INFORMATION

Dimensional stability	EN ISO 23999 (EN 434)		≤ 0,40	%
Curling	EN ISO 23999		≤ 8	mm
Light stability	EN ISO 105 B02		≥ 6 - 7	degree
Residual indentation	EN ISO 24343-1 (EN 433)		≤ 0,35	mm
Impact sound improvement	EN ISO 717/2		Δ Lw 16	dB
Dynamic coefficient of friction	EN 13893	DS	> 0,60	
Slip resistance (ramp test with oil)	DIN 51130	R10	R10	scale
Reaction to fire Report number ---- VNLF 031380.4	EN 13501-1	B_{fl}-s1	Bfl-s1	class
Underfloor heating	EN 12667		suitable	
Thermal resistance	ISO 8302		0,027	m².K/W
Thermal conductivity	EN 12524		0,09	W/(m.K)
Chemical resistance	ISO 26987 (EN 423)		resistant	
Static electrical propensity	EN 1815		< 2kV	on concrete
Pendulum test	CENTS 15676:2007		48+	
Cold welding	Werner Müller		type A	

* check individual ref. for available widths

Please note that the data given could be imprecise and liable to modifications of a technical nature at any time. The information in these documents is valid from 24/02/2023 and Beauflor reserve the right to make changes at any moment and without prior notice. Our technology is constantly evolving, so before carrying out any projects we encourage you to contact us to maintain our highest level of standards.

SUSTAINABILITY

We feel that it's our moral duty to contribute to a more sustainable world. This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment.

Ortho-phthalates free

100% Recyclable.

- No heavy metals
- No solvents
- No formaldehyde
- No harmful plasticizers

E1 APPROVED FOR EMISSIONS — Level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m3 of air)

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A B C — Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)

floor score

9 BB Ausschuss zur gesundheitlichen Bewertung von Bauprodukten

Certifié ISO 14001 Slovenian plant

Certifié ISO 9001 Slovenian/ Belgian plant

FEATURES

EN 14041
CE
05
DOP: 450-TC0013-1
B.I.G. Floorcoverings NV
Rijksweg 442, 8710 Wielsbeke
BELGIUM
NB: 0534
Resilient floor covering for use within building
DS B_{fl}-s1

TEX BAC · PREMIUM COATING · PENDULUM TEST · SLIP RESISTANCE R10 CLASSIFICATION · DIGITAL PRINT · NATURAL LOOK · SLIP RESISTANT · UNDERFLOOR HEATING · WARRANTY 7 YEAR RESIDENTIAL